

Millennium Expert/Enterprise

Technical Bulletin 029

08-19-2015

Title: Restoring a Converted Database for Expert/Enterprise v5.0

Contents: This technical bulletin explains how to restore Expert/Enterprise v5.0 databases after they have been converted from an older version of Millennium.

Procedure:

- 1. After Millennium has converted your databases and you have downloaded the converted.zip file from the FTP site, extract the contents of the zip file to the hard drive on the Millennium server.
- 2. From the Start Menu, run **SQL Server Management Studio**. Ensure that the server name and SQL instance are correct and click **Connect**.

🚽 Connect to Server	>	×
õõt se	erver 2012	
Server type:	Database Engine	/
Server name:	MSTASIO\SQLEXPRESS	~
Authentication:	Windows Authentication	/
User name:	SYNERGISTICS\Mstasio	-
Password:		
	Remember password	
Connect	Cancel Help Options >>	

3. In the left hand pane, expand **Databases** and select **MillArchiveModel**. Right-click on it and select **Tasks > Restore > Database**.

Databases Databases	abases in2 og2 New Database New Query Script Database as		
📧 🖿 Security	Tasks 🔸	Detach	
📧 🖿 Server Objec	Policies +	Take Offline	
Replication	Facets	Bring Online	
📧 🖻 Managemen	Start PowerShell	Shrink •	
	Reports +	Back Up	
	Rename	Restore +	Database
	Delete	Generate Scripts	Files and Filegroups
	Refresh	Extract Data-tier Application	Transaction Log
	Properties	Deploy Database to SQL Azure	
		Export Data-tier Application	
		Register as Data-tier Application	
		Upgrade Data-tier Application	
		Delete Data-tier Application	
		Import Data	
		Export Data	

4. A **Restore Database** screen will be displayed. Under **Source**, select the **Device** radio button. Click the ellipse button.

Select a page General	Script - E Help					
General	Script - Help Source					
📽 Files	Source					
	O Databasa:					
IF Options	O Database.					~
	Device:					
	Database:					~
	Destination					
	Data <u>b</u> ase:					~
	<u>R</u> estore to:				Iimeli	ne
	Restore plan					
	Backup sets to restore:					
Connection चार्थ्य connection properties	5					>
Progress	•					
Ready				Verif		/ledia
			ОК	Cancel	Help	J

5. A Select backup devices screen will be displayed. Click Add.

Select backup devices					×
Specify the backup media and its loca					
<u>B</u> ackup media type:	File	\sim			
Backup <u>m</u> edia:					
				<u>A</u> dd	
				<u>R</u> emove	
				Con <u>t</u> ents	
	<u>O</u> K	Canc	el	Help	

 Browse to the folder in which you extracted the converted databases to. Select MillArchiveModel.bak and click OK. This will return you to the Select backup devices screen. Click OK again.

Select backup devices					×
Specify the backup media and its k	ocation for your restore operation.				
<u>B</u> ackup media type:	File	\sim			
Backup <u>m</u> edia:					
C:\Backups\Converted\Converted\I	MillArchiveModel.bak			Add	
		[<u>R</u> emove	
		[Con <u>t</u> ents	
		•			
	<u> </u>	Cano	cei	Неір	

7. The **Restore Database** screen will be displayed again. In the left-pane, click on **Options**. Check the checkbox labelled **Overwrite the existing database (WITH REPLACE)** and then click **OK**.

	Restore Data	base - MillArchiveModel				×				
Select acade Generation Select acade Secrept - 18 Help Restore options Select acade Secrept - 18 Help Restore options Secrept - 18 Help Rest	0 Readv									
Files Portions Restore options	Select a page General	🖾 Script 🕞 🖪 Help								
Options Option	📽 Files	Restore options								
Connection Connection <td>Options</td> <td>Qverwrite the existing of t</td> <td>atabase (WITH REPLACE)</td> <td></td> <td></td> <td></td>	Options	Qverwrite the existing of t	atabase (WITH REPLACE)							
Connection properties Prompt Prompt Connection properties OK Cancel		Preserve the replication	settings (WITH KEEP_REPLICATION)							
Recovery state: RESTORE WITH RECOVERY Standby file: c:\Program Files\Microsoft SQL Server\MSSQL11.SQLEXPRESS\MSSQL\Backup\Mi Leave the database ready to use by rolling back uncommitted transactions. Additional transaction logs cannot be restored. Tail-Log backup Leave source database in the restoring state Leave connections Connection Prompt Prompt Leave source database Prompt The Full-Text Upgrade server property controls whether full-text indexes are imported, rebuilt, or reset for the restored database. OK Cancel Help		Restrict access to the restored database (WITH RESTRICTED LISER)								
Recovery state: RESTORE WITH RECOVERY Standby file: c\Program Files\Microsoft SQL Server\MSSQL11.SQLEXPRESS\MSSQL\Backup\Mi Leave the database ready to use by rolling back uncommitted transactions. Additional transaction logs cannot be restored. Tail-Log backup Tail-Log backup Leave source database in the restoring state Leave source database in the restoring state (WTH NORECOVERY) Backup file: Close existing connections Close existing connections to destination database Prompt Prompt Prompt One OK Cancel Help Help										
Standby file: c:\Program Files\Microsoft SQL Server\MSSQL11.SQLEXPRESS\MSSQL\Backup\Mi Leave the database ready to use by rolling back uncommitted transactions. Additional transaction logs cannot be restored. Tail-Log backup Leave source database in the restoring state Connections Connections Prompt Prompt The Full-Text Upgrade server property controls whether full-text indexes are imported, rebuilt, or reset for the restored database. OK Cancel Help		R <u>e</u> covery state:	RESTORE WITH RECOVERY							
Connection View Or Prompt Prompt Prompt Or Prompt Or Or Or Or Or Or Or Or Or Or Or Or Or Or Or Or Or Or Or Or		<u>S</u> tandby file:	c:\Program Files\Microsoft SQL Server\MSSQL11.SQLEXPRESS\MSSQL	\Backup\	Mi					
Tail-Log backup Iske tail-log backup before restore Leave source database in the restoring state (WTH NORECOVERY) Backup file: c\Program Files\Microsoft SQL Server\MSSQL11.SQLEXPRESS\MSSQL\Backup\Mi Server connections Close existing connections to destination database Prompt Prompt before restoring each backup Image: Connection street on the restoring state before restoring each backup Image: Connection street on the restoring each backup Image: Connection st		Leave the database ready	to use by rolling back uncommitted transactions. Additional transaction logs ca	nnot be r	restored.					
Tail-Log backup Jake tail-log backup before restore Leave source database in the restoring state (WITH NORECOVERY) Backup file: c\Program Files\Microsoft SQL Server\MSSQL11.SQLEXPRESS\MSSQL\Backup\Mi Server connections Close existing connections to destination database Prompt Prompt before restoring each backup I he Full-Text Upgrade server property controls whether full-text indexes are imported, rebuilt, or reset for the restored database.										
Connection Miew Connection Prompt before restoring each backup Microsoft SQL Server/MSSQL11.SQLEXPRESS/MSSQL/Backup/Mi Server connections connections to destination database Prompt connection Miew Connection Prompt before restoring each backup Microsoft SQL Server/MSSQL11.SQLEXPRESS/MSSQL/Backup/Mi Connection Miew Miew Connection Miew C		Tail-Log backup								
Connection View On nection OK Cancel Help			fore restore							
Backup file: c:\Program Files\Microsoft SQL Server\MSSQL11.SQLEXPRESS\MSSQL\Backup\Mi Server connections Connection Connection Prompt Prompt before restoring each backup I he Full-Text Upgrade server property controls whether full-text indexes are imported, rebuilt, or reset for the restored database. Promress I Done OK Cancel		□ <u>L</u> eave source data (WITH NORECOVI	ibase in the restoring state :RY)							
Server connections Connection Prompt Prompt before restoring each backup Image: Definition of the server property controls whether full-text indexes are imported, rebuilt, or reset for the restored database. Promettion. Prompt before restoring each backup Image: Definition of the server property controls whether full-text indexes are imported, rebuilt, or reset for the restored database.		<u>B</u> ackup file:	c:\Program Files\Microsoft SQL Server\MSSQL11.SQLEXPRESS\MSSQL	\Backup\	Mi					
□ Close existing connections to destination database Prompt □ Prompt before restoring each backup ① The Full-Text Upgrade server property controls whether full-text indexes are imported, rebuilt, or reset for the restored database. Prooress ② Done OK Cancel		Server connections				_				
Connection View. connection view. connection. properties Prooress		Close existing connection	ons to destination database							
Connection Image: Prompt Image: Prompt before restoring each backup Image: Prompt bef										
Connection View. connection properties Process © Done OK Cancel Help		Dromot								
Connection Image: Deficie restoring each backup View. Image: Deficie restoring each backup Image: Connection properties Image: Deficie restoring each backup Progress Image: Deficie restoring each backup Image: Open controls Image: Deficie restoring each backup Image: Open control of the progress Image: Deficie restoring each backup Image: Open control of the progress Image: Deficie restoring each backup Image: Open control of the progress Image: Deficie restoring each backup Image: Open contrestoring each backup Image: Deficie rest			u oach hackup							
wiew connection properties Procress ⊘ Done	Connection		, each backup	ant for th		a d				
connection properties Procress ⊗ Done OK Cancel Help	<u>∛iew</u>	database.	as server property controls whether run-text indexes are imported, rebuilt, of re	set for tr	ie restor	ea				
Progress Ø Done OK Cancel Help	properties									
OK Cancel Help	Progress									
OK Cancel Help	V Done									
OK Cancel Help										
			OK Cance	əl	Help	c				

8. SQL Server will begin to restore the database. Once completed, a message will be displayed indicating that the database was successfully restored. Click **OK** to complete the process.



9. Repeat steps 3 through 8 for the MillCfg, MillHist and MillPlus databases. Make sure to select the correct database in step 3 and step 6. Note that the MillHist database is typically the largest database and may take longer to complete the restore.